# SAFETY DATA SHEET

# 1. Identification

Product identifier	Socket Lock - Resin/ Part	A (as part of a 2 component kit)
Other means of identification		
SKU#	MI040R	
Recommended use	Not available.	
<b>Recommended restrictions</b>	None known.	
Manufacturer/Importer/Supplier	/Distributor information	
Manufacturer		
Company name	ITW Performance Polymers	
Address	130 Commerce Drive	
	Montgomeryville, PA 18936	
	United States	
Telephone	Customer Service 215-855-8450	
Website	www.itwperformancepolymers.com	
E-mail	Not available.	
Contact person	EHS Department	
Emergency phone number	CHEMTREC	800-424-9300
	International	703-527-3887

## 2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Warning
Hazard statement	Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Hazard(s) not otherwise classified (HNOC) Supplemental information

4 First-aid measures

Dispose of contents/container in accordance with local/regional/national/international regulations.

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

81.7% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 81.7% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Quartz		14808-60-7	30 - 60
Polyester Resin		26098-37-3	10 - 30
Styrene		100-42-5	10 - 30
Other components below r	eportable levels		1 - < 3

4. First-alu measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	

#### Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water jet as an extinguisher, as this will spread the fire. Unsuitable extinguishing media Specific hazards arising from Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source the chemical of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire. and precautions for firefighters Fire fighting In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. equipment/instructions **Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards Flammable liquid and vapor.

## 6. Accidental release measures

6. Accidental release mea	30163
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
	For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
8. Exposure controls/pers	onal protection
	-

#### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)				
Components	Туре	Value	Form	
Quartz (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.	

Components	Тур	its (PEL) (29 CFR 1 e		alue	
STYRENE (CAS 100-42-5)	Ceil	ing	20	0 ppm	
	TWA	4	10	0 ppm	
US. OSHA Table Z-3 Perm Components	issible Exposure Lim Typ			R 1910.1000) alue	Form
Quartz (CAS 14808-60-7)	TWA	A	0.1	1 mg/m3	Respirable.
			2.4	4 mppcf	Respirable.
US. ACGIH Threshold Lim Components	it Values (TLV) Typ	e	Va	alue	Form
Quartz (CAS 14808-60-7)	TWA	4	0.0	025 mg/m3	Respirable fraction.
STYRENE (CAS 100-42-5)	STE	L	20	ppm	
	TWA	A	10	) ppm	
NIOSH. Immediately Dang Components	erous to Life or Healt Typ	. , , ,		alue	
Quartz (CAS 14808-60-7)	IDLI		50	) mg/m3	
STYRENE (CAS 100-42-5)	IDLI			9 %	
(				0 ppm	
US. NIOSH: Pocket Guide	to Chemical Hazards	Recommended Ex		••	
Components	Тур		-	alue	Form
Quartz (CAS 14808-60-7)	TWA	4	0.0	05 mg/m3	Respirable dust.
STYRENE (CAS 100-42-5)	STE	L	42	25 mg/m3	
. ,				-	
. ,			10	0 ppm	
. ,	TWA	Ą		0 ppm 5 mg/m3	
. ,	TWA	Ą	21		
logical limit values	TW	A	21	5 mg/m3	
		A Determinant	21	5 mg/m3	Time
logical limit values ACGIH Biological Exposu	re Indices (BEI) Value		21 50	5 mg/m3 ) ppm	Time
logical limit values ACGIH Biological Exposur Components STYRENE (CAS 100-42-5)	re Indices (BEI) Value	Determinant	21 50 <b>Specimen</b>	5 mg/m3 ) ppm Sampling	Time
logical limit values ACGIH Biological Exposur Components STYRENE (CAS 100-42-5)	re Indices (BEI) Value 40 μg/l	Determinant Styrene	21 50 <b>Specimen</b> Urine	5 mg/m3 ) ppm Sampling	Time
logical limit values ACGIH Biological Exposur Components STYRENE (CAS 100-42-5)	re Indices (BEI) Value 40 μg/l 400 mg/g	Determinant Styrene Mandelic acid plus phenylglyoxylic acid	21 50 <b>Specimen</b> Urine Creatinine in	5 mg/m3 ) ppm Sampling	Time
logical limit values ACGIH Biological Exposur Components STYRENE (CAS 100-42-5)	re Indices (BEI) Value 40 μg/l 400 mg/g	Determinant Styrene Mandelic acid plus phenylglyoxylic acid	21 50 <b>Specimen</b> Urine Creatinine in	5 mg/m3 ) ppm Sampling	Time
Iogical limit values ACGIH Biological Exposur Components STYRENE (CAS 100-42-5) * - For sampling details, plea	re Indices (BEI) Value 40 μg/l 400 mg/g ase see the source doo	Determinant Styrene Mandelic acid plus phenylglyoxylic acid cument.	21 50 <b>Specimen</b> Urine Creatinine in urine	5 mg/m3 ) ppm Sampling * *	Time
ACGIH Biological Exposure Components STYRENE (CAS 100-42-5) * - For sampling details, plea posure guidelines US - California OELs: Skin Styrene (CAS 100-42-5	re Indices (BEI) Value 40 μg/l 400 mg/g ase see the source doo designation	Determinant Styrene Mandelic acid plus phenylglyoxylic acid cument.	21 50 <b>Specimen</b> Urine Creatinine in	5 mg/m3 ) ppm Sampling * *	Time
ACGIH Biological Exposur Components STYRENE (CAS 100-42-5) * - For sampling details, plea oosure guidelines US - California OELs: Skin Styrene (CAS 100-42-5 US - Minnesota Haz Subs:	re Indices (BEI) Value 40 μg/l 400 mg/g ase see the source doo designation ) Skin designation ap	Determinant Styrene Mandelic acid plus phenylglyoxylic acid cument. Can be	21 50 Specimen Urine Creatinine in urine	5 mg/m3 9 ppm Sampling * * *	Time
ACGIH Biological Exposur Components STYRENE (CAS 100-42-5) * - For sampling details, plea oosure guidelines US - California OELs: Skin Styrene (CAS 100-42-5 US - Minnesota Haz Subs: Styrene (CAS 100-42-5	re Indices (BEI) Value 40 μg/l 400 mg/g ase see the source doo designation ) Skin designation ap	Determinant Styrene Mandelic acid plus phenylglyoxylic acid cument. Can be plies Skin de	21 50 Specimen Urine Creatinine in urine	5 mg/m3 9 ppm Sampling * * *	
ACGIH Biological Exposur Components STYRENE (CAS 100-42-5) * - For sampling details, plea oosure guidelines US - California OELs: Skin Styrene (CAS 100-42-5 US - Minnesota Haz Subs:	re Indices (BEI) Value 40 µg/l 400 mg/g ase see the source doo designation ) Skin designation app ) Explosion-proof ge Ventilation rates sh exhaust ventilation exposure limits. If o	Determinant Styrene Mandelic acid plus phenylglyoxylic acid cument. Can be plies Skin de eneral and local exha nould be matched to , or other engineerin	21 50 Specimen Urine Creatinine in urine e absorbed throu esignation applie ust ventilation. conditions. If ap g controls to ma not been estab	5 mg/m3 ppm Sampling * * * ugh the skin. es. Good general pplicable, use aintain airborn lished, mainta	ventilation should be used process enclosures, local
ACGIH Biological Exposur Components STYRENE (CAS 100-42-5) * - For sampling details, plea oosure guidelines US - California OELs: Skin Styrene (CAS 100-42-5 US - Minnesota Haz Subs: Styrene (CAS 100-42-5 oropriate engineering	re Indices (BEI) Value 40 µg/l 400 mg/g ase see the source doo designation ) Skin designation app ) Explosion-proof ge Ventilation rates sh exhaust ventilation exposure limits. If of acceptable level. F s, such as personal p	Determinant Styrene Mandelic acid plus phenylglyoxylic acid cument. Can be plies Skin de eneral and local exha nould be matched to , or other engineerin exposure limits have Provide eyewash stat	21 50 Specimen Urine Creatinine in urine e absorbed throu esignation applie ust ventilation. If ap g controls to ma not been estab ion and safety s nt	5 mg/m3 ppm Sampling * * * * ugh the skin. es. Good general pplicable, use aintain airborna lished, mainta shower.	ventilation should be used process enclosures, local e levels below recommend
<ul> <li>Iogical limit values</li> <li>ACGIH Biological Exposure Components</li> <li>STYRENE (CAS 100-42-5)</li> <li>* - For sampling details, pleaters</li> <li>Styrene (CAS 100-42-5)</li> <li>US - California OELs: Sking Styrene (CAS 100-42-5)</li> <li>US - Minnesota Haz Subs: Styrene (CAS 100-42-5)</li> <li>oropriate engineering introls</li> </ul>	re Indices (BEI) Value 40 μg/l 400 mg/g ase see the source door a designation ) Skin designation app ) Explosion-proof get Ventilation rates sh exhaust ventilation exposure limits. If a acceptable level. F s, such as personal p Chemical respirator	Determinant Styrene Mandelic acid plus phenylglyoxylic acid cument. Can be plies Skin de neral and local exha hould be matched to , or other engineerin exposure limits have provide eyewash stat	21 50 Specimen Urine Creatinine in urine absorbed throu esignation applie sust ventilation. conditions. If ap g controls to ma not been estab cion and safety s nt cartridge and fu	5 mg/m3 ppm Sampling * * * * ugh the skin. es. Good general pplicable, use aintain airborna lished, mainta shower.	ventilation should be used process enclosures, local e levels below recommend
Iogical limit values ACGIH Biological Exposur Components STYRENE (CAS 100-42-5) * - For sampling details, pleat bosure guidelines US - California OELs: Skin Styrene (CAS 100-42-5) US - Minnesota Haz Subs: Styrene (CAS 100-42-5) oropriate engineering itrols ividual protection measures Eye/face protection Skin protection	re Indices (BEI) Value 40 µg/l 400 mg/g ase see the source doo designation ) Skin designation app ) Explosion-proof ge Ventilation rates sh exhaust ventilation exposure limits. If of acceptable level. F s, such as personal p Chemical respirato Wear appropriate of	Determinant Styrene Mandelic acid plus phenylglyoxylic acid cument. Can be plies Skin de eneral and local exha nould be matched to , or other engineerin exposure limits have Provide eyewash stat protective equipmen or with organic vapor chemical resistant gl	21 50 Specimen Urine Creatinine in urine e absorbed throu esignation applie ust ventilation. If ap g controls to ma not been estab ion and safety s nt cartridge and fu	5 mg/m3 9 ppm Sampling * * * * ugh the skin. es. Good general pplicable, use aintain airborn- lished, mainta shower. ull facepiece.	ventilation should be used process enclosures, local e levels below recommend
Iogical limit values ACGIH Biological Exposur Components STYRENE (CAS 100-42-5) * - For sampling details, plea osure guidelines US - California OELs: Skin Styrene (CAS 100-42-5 US - Minnesota Haz Subs: Styrene (CAS 100-42-5 oropriate engineering itrols ividual protection measures Eye/face protection Skin protection Hand protection	re Indices (BEI) Value 40 μg/l 400 mg/g ase see the source door a designation ) Skin designation app ) Explosion-proof ge Ventilation rates sh exhaust ventilation exposure limits. If of acceptable level. F s, such as personal p Chemical respirato Wear appropriate of Wear appropriate of	Determinant Styrene Mandelic acid plus phenylglyoxylic acid cument. Can be plies Skin de eneral and local exha nould be matched to , or other engineerin exposure limits have Provide eyewash stat protective equipmen or with organic vapor chemical resistant gl	21 50 Specimen Urine Creatinine in urine e absorbed throu esignation applie ust ventilation. conditions. If ap g controls to ma not been estab ion and safety s nt cartridge and fu oves. othing. Use of a	5 mg/m3 9 ppm Sampling * * * ugh the skin. es. Good general pplicable, use aintain airborna- lished, mainta shower. ull facepiece. n impervious a	ventilation should be used process enclosures, local e levels below recommend in airborne levels to an

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

5.1 Hysical and chemical	
Appearance	Liquid.
Physical state	Liquid.
Form	Liquid.
Color	Green
Odor	Pungent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	293.54 °F (145.3 °C) estimated
Flash point	90.0 °F (32.2 °C) Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	1.1 % estimated
Explosive limit - upper (%)	6.1 % estimated
Vapor pressure	8.53 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	914 °F (490 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.60 g/cm3
Explosive properties	Not explosive.
Flammability class	Flammable IC estimated
Oxidizing properties	Not oxidizing.
Specific gravity	1.6
VOC	46.36 % estimated

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Aluminum. Peroxides.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

### Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

## Information on toxicological effects

A suite texticity		
Acute toxicity	Not known.	
Components	Species	Test Results
Styrene (CAS 100-42-5)		
<u>Acute</u> Oral		
LD50	Rat	1 g/kg
Skin corrosion/irritation	Causes skin irritation.	99
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization	1	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to	o cause skin sensitization.
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	product or any components present at greater than 0.1% are
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall E	Evaluation of Carcinogenicity	
Quartz (CAS 14808-60-7) Styrene (CAS 100-42-5) OSHA Specifically Regulate	d Substances (29 CFR 1910.1	1 Carcinogenic to humans. 2A Probably carcinogenic to humans. 001-1053)
Quartz (CAS 14808-60-7)	•	Cancer
(	gram (NTP) Report on Carcin	ogens
Quartz (CAS 14808-60-7) Styrene (CAS 100-42-5)		Known To Be Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.
Reproductive toxicity	This product is not expected to	o cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be l	narmful. Prolonged exposure may cause chronic effects.
12. Ecological information	1	
Ecotoxicity	Harmful to aquatic life with lor	ig lasting effects.

harmun to aquatic me with ong lasting enects.		
No data is available on the degradability of any ingredients in the mixture.		
ol / water (log Kow) 2.95		
No data available.		
The product contains volatile organic compounds which have a photochemical ozone creation potential.		

#### 13. Disposal considerations **Disposal instructions** Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. Local disposal regulations Dispose in accordance with all applicable regulations. D001: Waste Flammable material with a flash point <140 F Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Dispose of in accordance with local regulations. Empty containers or liners may retain some Waste from residues / unused product residues. This material and its container must be disposed of in a safe manner (see: products

Contaminated packaging

product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

DOT	
UN number	UN3269
UN proper shipping name	Polyester resin kit, liquid base material
Transport hazard class(es)	
Class	3
Subsidiary risk	
Label(s)	3
Packing group	-
Environmental hazards	
Marine pollutant	No.
•	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	40, 149
Packaging exceptions	165
Packaging non bulk	165
Packaging bulk	None
ΙΑΤΑ	
UN number	UN3269
UN proper shipping name	Polyester resin kit liquid base material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN3269
UN proper shipping name	POLYESTER RESIN KIT, liquid base material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according toNot established.Annex II of MARPOL 73/78 andthe IBC Code

DOT



# 15. Regulatory information

_				
US federal regulations	This product is a "H Standard, 29 CFR 1		fined by the OSHA Hazard	Communication
US EPCRA (SARA Title	III) Section 313 - Tox	kic Chemical: De minimis	concentration	
Styrene (CAS 100-4		% 0.1		
US EPCRA (SARA Title	III) Section 313 - Tox	tic Chemical: Listed sub	stance	
Styrene (CAS 100-4	2-5)	Listed.		
Toxic Substances Control	Act (TSCA)			
TSCA Section 12(b) Ex	port Notification (40	CFR 707, Subpt. D)		
Not regulated.				
CERCLA Hazardous Substa	ance List (40 CFR 302	2.4)		
Styrene (CAS 100-42-5)		Listed.		
SARA 304 Emergency relea	se notification			
Not regulated.				
OSHA Specifically Regulate	ed Substances (29 CF	FR 1910.1001-1053)		
Quartz (CAS 14808-60-7	')	Cancer lung effects immune syste kidney effects	m effects	
Superfund Amendments and Re	eauthorization Act of	1986 (SARA)		
SARA 302 Extremely hazar				
Not listed.				
SARA 311/312 Hazardous chemical	Yes			
Classified hazard categories	Skin corrosion or irr Serious eye damage Carcinogenicity		)	
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Styrene		100-42-5	10 - 30	

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Styrene (CAS 100-42-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Styrene (CAS 100-42-5)

Other Flavoring Substances with OSHA PEL's

#### **US state regulations**

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Quartz (CAS 14808-60-7) Styrene (CAS 100-42-5)

#### **California Proposition 65**



**WARNING:** This product can expose you to chemicals including Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (CAS 14808-60-7)	Listed: October 1, 1988
Styrene (CAS 100-42-5)	Listed: April 22, 2016
Titanium Dioxide (CAS 13463-67-7)	Listed: September 2, 2011

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	10-09-2023
Version #	01
HMIS® ratings	Health: 2* Flammability: 3 Physical hazard: 1 Personal protection: X
NFPA ratings	Health: 2 Flammability: 3 Instability: 1

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

# SAFETY DATA SHEET

# 1. Identification

Product identifier	Socket Lock - Hardener/ Part B (as part of 2 component kit)		
Other means of identification			
SKU#	MI040H		
Recommended use	Not available.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplie	r/Distributor information		
Manufacturer			
Company name	ITW Performance Polymers		
Address	130 Commerce Drive		
	Montgomeryville, PA 18936		
	United States		
Telephone	Customer Service	215-855-8450	
Website	www.itwperformancepolyme	ers.com	
E-mail	Not available.		
Contact person	EHS Department		
Emergency phone number	CHEMTREC	800-424-9300	
	International	703-527-3887	

## 2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 4
Health hazards	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 4
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Warning	
Hazard statement	Combustible liquid. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.	
Precautionary statement		
Prevention		o smoking. Avoid breathing mist/vapors. Wash clothing must not be allowed out of the workplace. ctive gloves/protective clothing/eye protection/face
Response	If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.	
Storage	Store in a well-ventilated place. Keep cool.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/informatio	on on ingredients		
Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Dibenzoyl Peroxide		94-36-0	30 - 60
Other components below report	able levels		30 - 60
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if symptom	ns develop or persist.	
Skin contact	Remove contaminated clothing immediately a eczema or other skin disorders: Seek medica	al attention and take along thes	e instructions.
Eye contact	Immediately flush eyes with plenty of water for present and easy to do. Continue rinsing. Ge	t medical attention if irritation d	
Ingestion	Rinse mouth. Get medical attention if sympto		
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include vision. May cause an allergic skin reaction. D		lling, and blurred
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and tre Symptoms may be delayed.	at symptomatically. Keep victir	n under observation.
General information	Ensure that medical personnel are aware of t protect themselves. Wash contaminated cloth		ke precautions to
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carb	oon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as th	is will spread the fire.	
Specific hazards arising from the chemical	The product is combustible, and heating may mixtures. During fire, gases hazardous to heat		rm explosive vapor/ai
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full p	rotective clothing must be worr	n in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.		
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.		
General fire hazards	Combustible liquid.		
6. Accidental release mea	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep pe ignition sources (no smoking, flares, sparks, or protective equipment and clothing during clear damaged containers or spilled material unles adequate ventilation. Local authorities should contained. For personal protection, see section	or flames in immediate area). V an-up. Avoid breathing mist/vap s wearing appropriate protectiv I be advised if significant spillag	Vear appropriate oors. Do not touch e clothing. Ensure
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, fla combustibles (wood, paper, oil, etc.) away fro drains.		
	Large Spills: Stop the flow of material, if this i possible. Use a non-combustible material like and place into a container for later disposal. I	e vermiculite, sand or earth to s	oak up the product
	Small Spills: Absorb with earth, sand or other for later disposal. Wipe up with absorbent ma remove residual contamination.		
Environmental precautions	Never return spills to original containers for re Avoid release to the environment. Inform app environmental releases. Prevent further leake drains, water courses or onto the ground.	propriate managerial or supervis	sory personnel of all

7. Handling and storage			
Precautions for safe handling	Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.		
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).		
8. Exposure controls/per	sonal protection		
Occupational exposure limits			
	e the only constituents of the product whi uents have no known exposure limits.	ich have a PEL, TLV or other recommended exposure limit.	
US. OSHA Table Z-1 Permis Components	ssible Exposure Limits (PEL) for Air C Type	ontaminants (29 CFR 1910.1000) Value	
Dibenzoyl Peroxide (CAS 94-36-0)	PEL	5 mg/m3	
US. ACGIH Threshold Limit Components	t Values (TLV) Type	Value	
Dibenzoyl Peroxide (CAS 94-36-0)	TWA	5 mg/m3	
NIOSH. Immediately Dange Components	rous to Life or Health (IDLH) Values, a Type	s amended Value	
Dibenzoyl Peroxide (CAS 94-36-0)	IDLH	1500 mg/m3	
,	o Chemical Hazards Recommended E Type	xposure Limits (REL) Value	
Dibenzoyl Peroxide (CAS 94-36-0)	TWA	5 mg/m3	
Biological limit values	No biological exposure limits noted for	r the ingredient(s).	
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.		
Individual protection measures Eye/face protection	, such as personal protective equipme Wear safety glasses with side shields	ent (or goggles). Face shield is recommended.	
Skin protection Hand protection	Wear appropriate chemical resistant g	loves.	
Other	Wear appropriate chemical resistant of	lothing. Use of an impervious apron is recommended.	
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.		
Thermal hazards	Wear appropriate thermal protective c	lothing, when necessary.	
General hygiene considerations	after handling the material and before	serve good personal hygiene measures, such as washing eating, drinking, and/or smoking. Routinely wash work emove contaminants. Contaminated work clothing should no	
9. Physical and chemical	properties		
•	Liquid		

Appearance	Liquid.
Physical state	Liquid.
Form	Liquid.
Color	White
Odor	Sweet
Odor threshold	Not available.

рН	Not available.
Melting point/freezing point	217.4 °F (103 °C) estimated
Initial boiling point and boiling range	Not available.
Flash point	>184.0 °F (>84.4 °C) Setaflash
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.00009 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	176 °F (80 °C) estimated
Decomposition temperature	>122 °F (>50 °C) (Heat accumulation storage test) - Self-Accelerating Decomposition Temperature (SADT)
Viscosity	Not available.
Other information	
Density	1.10 g/cm3
Explosive properties	Not explosive.
Flammability class	Combustible IIIA estimated
Oxidizing properties	Not oxidizing.
Specific gravity	1.1
40 Otability and seativity	

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Alcohols. Amines.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

## Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.
Information on toxicological ef	fects

Acute toxicity

Not known.

Components	Species	Test Results
Dibenzoyl Peroxide (CAS 94-36-0	)	
<u>Acute</u>		
Oral		
LD50	Rat	7710 mg/kg
Skin corrosion/irritation	Prolonged skin contact may	cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation	۱.
Respiratory or skin sensitization	n	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin i	eaction.
Germ cell mutagenicity	No data available to indicate mutagenic or genotoxic.	e product or any components present at greater than 0.1% are
Carcinogenicity	Not classifiable as to carcin	ogenicity to humans.
IARC Monographs. Overall	Evaluation of Carcinogenici	ty
Not listed.	ed Substances (29 CFR 1910	
Not listed.	ogram (NTP) Report on Carc	แบบสแอ
Reproductive toxicity	This product is not expected	to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may b	e harmful.
12. Ecological informatio	n	
Ecotoxicity	Harmful to aquatic life. May	cause long lasting harmful effects to aquatic life.
Persistence and degradability	No data is available on the	degradability of any ingredients in the mixture.
Bioaccumulative potential		
Partition coefficient n-octar Dibenzoyl Peroxide	nol / water (log Kow)	3.46
Mobility in soil	No data available.	
Other adverse effects		ental effects (e.g. ozone depletion, photochemical ozone creation on, global warming potential) are expected from this component.
13. Disposal consideration	ons	
Disposal instructions	this material to drain into se	use in sealed containers at licensed waste disposal site. Do not allow wers/water supplies. Do not contaminate ponds, waterways or ditches iner. Dispose of contents/container in accordance with national regulations.
Local disposal regulations	Dispose in accordance with	all applicable regulations.
Hazardous waste code	The waste code should be a disposal company.	assigned in discussion between the user, the producer and the waste
Waste from residues / unused products		ith local regulations. Empty containers or liners may retain some rial and its container must be disposed of in a safe manner (see:
Contaminated packaging		ay retain product residue, follow label warnings even after container is should be taken to an approved waste handling site for recycling or
14. Transport information	· · · · · ·	

## DOT

UN number

UN proper shipping name Transport hazard class(es)	Polyester resin kit, liquid base material
Class	3
	-
Subsidiary hazard	3
Label(s) Packing group	-
Environmental hazards	
Marine pollutant	No.
•	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	40, 149
Packaging exceptions	165
Packaging non bulk	165
Packaging bulk	None
IATA	
UN number	UN3269
UN proper shipping name	Polyester resin kit liquid base material
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN3269
UN proper shipping name	POLYESTER RESIN KIT, liquid base material
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and the IBC Code	
DOT	





#### 15. Regulatory information **US** federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration Dibenzoyl Peroxide (CAS 94-36-0) % 1.0 US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance Dibenzoyl Peroxide (CAS 94-36-0) Listed. **Toxic Substances Control Act (TSCA)** TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical	Yes
Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Serious eye damage or eye irritation Respiratory or skin sensitization

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Dibenzoyl Peroxide	94-36-0	30 - 60

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

## US state regulations

## **California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

Country(s) or region	Inventory name On	inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
* A UN / U !	a set of this was due to see the with the increase we wind a set of sinistened by the second second	· · · · · · · · · · · · · · · · · · ·

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	11-29-2023
Revision date	02-28-2024
Version #	02
HMIS® ratings	Health: 2 Flammability: 2 Physical hazard: 2
NFPA ratings	Health: 2 Flammability: 2 Instability: 2
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.
Revision information	Stability and reactivity: Conditions to avoid